

Softner Towel Conc.

DESCRIPTION

Prowick TS is a unique multi-purpose auxiliary water dispersible polyester polymer. The product is designed to impart several desirable properties to fabric including: wicking, absorbency, soil release, bath lubrication, detergency and oil scavenging

BENEFITS

Prowick TS has the following beneficial characteristics.

- Highly concentrated
- Economical use
- Highly versatile

TYPICAL PROPERTIES

Color	Opaque Beige
Texture	Thick Liquid
Ionic Nature	Nonionic

PREPARATION

Prowick TS is ready to use

APPLICATION

Prowick TS may be applied as follows.

Soil Release Finish: May be used alone at 2– 5% OWF or may be used to reduce (extend) Amount of fluorochemical finish by 30%.

Preparation Agent: May be use at 0.5 1%OWF in preparation bath as an oil scavenger. May also be used alone in dye bath at 2 – 5%OWF as sole Preparation agent for scouring 100% polyester.

Dyeing: May be used at 0.5 – 1 g/l as dye bath lubricant. May also be used at OWF in dye bath to lend wicking and absorbency to polyesters around 3-5%.over for solid release antistatic properties.

HANDLING

Follow good industrial hygiene when handling Prowick TS. Please refer to the Material Safety Data Sheet for details.

STORAGE

Prowick TS should be stored in a cool, dry and well-ventilated area.

PACKAGING

Prowick TS is available in 200 KGS drums.

Date Established:

Date Revised: